

WALTER A. TILLIT, JR., P.E.

tilteco@aol.com FL P.E. License No. 44167 FL E.B. License No. 0006719

PRODUCT EVALUATION REPORT

FL 12246

REPORT NO .:

09-1207.01

DATE:

December 07, 2009

PRODUCT CATEGORY:

Hurricane Shutters

PRODUCT SUB-CATEGORY:

Rolling Abatement

PRODUCT NAME:

Nautilus Rolling Abatement

SUBMITTED BY:

Expert Shutter Services, Inc. 1626 S.W. Biltmore Street Port St. Lucie, FL 34984

1. PURPOSE OF EVALUATION:

This is a Product Evaluation Report issued by Walter A. Tillit, Jr., P.E. (System ID # 1906) to Expert Shutter Services, Inc. based on Rule Chapter No. 9B-72.070, Method 1d of the State of Florida Product Approval, Department of Community Affairs-Florida Building Commission.

This product is being issued an Evaluation Report as described herein, and has been verified for compliance in accordance with the 2007 edition of the Florida Building Code, and to verify that the product is for the purpose intended at least equivalent to that required by the Code.

This Product Evaluation Report shall be subject to review and revision in case of a Building Code Change that may affect its limitations and conditions.

2. EVIDENCE SUBMITTED:

2.1. PRODUCT EVALUATION DOCUMENT (P.E.D.):

Drawing No. 09-210, titled "Nautilus Rolling Abatement", sheets 1 thru 26 of 26, including 10A,11A,12A, & 13A (Total = 30 sheets) prepared by Tilteco, Inc.; signed and sealed by Walter A. Tillit, Jr., P.E.; dated 12/03/09. This drawing is an integral part of this Evaluation Report.

2.2. TEST REPORTS:

Large missile impact and cyclic loading under TAS 201 & TAS 203 Protocols, as per section 1626 of the Florida Building Code. Uniform Static loads in accordance with Protocol TAS 202 of the Florida Building Code. Test reports prepared by American Test Lab of South Florida, Report No. 1030.01-08, signed and sealed by Henry Hattem, P.E.

141409

6355 N.W. 36th Street, Suite 305, Miami, Florida 33166 - Phone: (305) 871-1530 - Fax: (305) 871-1531

PRODUCT EVALUATION REPORT NO. 09-1207.01

and William R. Mehner, P.E. dated 02/13/09 and addendum dated 02/25/09.

Tensile Tests on Mechanical Properties of Slat, as per QC Metallurgical, Inc. No. 9AM-31, dated January 16, 2009, signed and sealed by Frank Grate, P.E., per ASTM E-8 and on stainless steel retaining screw, as per lab report No. 9AM-32, dated January 15, 2009, signed and sealed by Frank Grate, P.E. per ASTM E-8.

2.3. STRUCTURAL ENGINEERING CALCULATIONS:

On Nautilus Rolling Abatement for MAXIMUM span vs. design wind load, as well as anchor spacing vs. design wind load and Abatement span including mullions and storm bars, based on rational and comparative analysis, and in accordance with sections 1612 and 2003 of the Florida Building Code. Calculations prepared by Tilteco, Inc., dated 12/03/09, signed and sealed by Walter A. Tillit, Jr., P.E.

3. MISSILE IMPACT RESISTANCE:

Large missile impact under section 1626 of the Florida Building Code, as per TAS 201 Protocol (Large Missile).

4. WIND LOADS RESISTANCE:

Nautilus Rolling Abatement has been verified to sustain wind pressures. Slat Span shall be as indicated on sheets 15, 16 and 20 of Product Evaluation Document (P.E.D.), drawing No. 09-210. Maximum Anchor Spacing shall be as indicated on sheets 17, 18 and 21 of Product Evaluation Document (P.E.D.), drawing No. 09-210. Storm Bar and mullion span shall be as indicated on sheets 22 and 24 thru 26 respectively of Product Evaluation Document (P.E.D.), drawing # 09-210.

5. INSTALLATION:

Shall be strictly performed in accordance with the details indicated on sheets 4 6,5,7,8,9,10,10A,11,11A,12,12A,13 & 13A of Product Evaluation Document (P.E.D.), drawing No. 09-210. Minimum separation to glass shall be as indicated on sheets 15, 16 and 20 of Product Evaluation Document (P.E.D.), drawing No. 09-210.

6. MATERIAL CHARACTERISTICS AND SPECIFICATIONS:

Shall be strictly in accordance with General Notes and Components indicated on sheets 1, 2 and 3 of Product Evaluation Document (P.E.D.), drawing No. 09-210. Anchor specifications shall be as indicated on sheets 1, 8, 9, 10, 10A, 11, 11A, 12, 12A, 13, 13A and 21 of Product Evaluation Document (P.E.D.), drawing No. 09-210.

14/16/09

PRODUCT EVALUATION REPORT NO. 09-1207.01

7. LIMITATIONS AND CONDITIONS OF USE:

- 7.1. Shall be strictly in compliance with General Notes No. 2 and 11 thru 16, indicated on sheet 1, as well as details and notes on sheets 19 and 20 of Product Evaluation Document (P.E.D.), drawing No. 09-210 prepared by Tilteco, Inc. and signed and sealed by Walter A. Tillit, Jr., P.E.
- 7.2. Product **may** be installed within HIGH VELOCITY HURRICANE ZONES as defined on section 1620.2 of the Florida Building Code.
- 7.3. Product shall only be installed into poured concrete, grouted cell concrete block, and wood frame structures, as limited and defined on Product Evaluation Document No. 09-210.

Product Evaluation Report prepared by Walter A. Tillit, Jr., P.E. (Florida License No. 44167), President of Tilteco, Inc. (Florida EB-0006719).