

Crimsafe Products tested and Design Pressures

Safe-S-Cape:

| | |
|------------------------|-------------------------------------------------------------|
| Size tested: | 55" wide by 85" high (4' 7" x 7' 1") |
| Design Pressure: | ±75.0 psf with a 1.5 greater structural overload ±112.5 psf |
| Florida Building Code: | FL13259 |
| Miami Dade County NOA: | NOA 09-1005.03 |

Fixed Build-Out:

| | |
|------------------------|-------------------------------------------------------------|
| Size tested: | 53" wide by 85" high (4' 5" x 7' 1") |
| Design Pressure: | ±75.0 psf with a 1.5 greater structural overload ±112.5 psf |
| Florida Building Code: | FL#13779 |
| Miami Dade County NOA: | NOA 10-0504.04 |

Patio Enclosure:

| | |
|------------------------|------------------------------------------------------------|
| Size tested: | 187" wide by 144" high (15' 7" x 12') |
| Single Panel Size: | 61" wide by 96" high (5' 1" x 8' 0-3/8") |
| Design Pressure: | ±50.0 psf with a 1.5 greater structural overload ±75.0 psf |
| Florida Building Code: | FL#13770 |
| Miami Dade County NOA: | NOA 10-0706.04 |

Note: 2" x 6" x 1/4" vertical mullions, 2" x 1" x 1/8" horizontal mullions. One side was not secured for unlimited length. A single specimen was tested with horizontal midrail.

Hinge Door with top and bottom patio bolts for hurricane areas:

| | |
|------------------------|-----------------------------------------------------------------------------|
| Size tested: | 42" wide by 81" high (3' 6" x 6' 9") / 42" wide by 96" high (3' 6" x 8' 0") |
| Design Pressure: | ±50.0 psf with a 1.5 greater structural overload ±75.0 psf |
| Florida Building Code: | FL#13771 |
| Miami Dade County NOA: | NOA 10-0706.05 |

Note: 1 unit tested with a midrail, 4 units tested with full screen

Miami Dade County test protocols

TAS 201-94: *Impact Test Procedures (Large missile impact)*

TAS 202-94: *Criteria for testing Impact and None Impact Resistant Building Envelope Components Using Uniform Static Air Pressure Loading (Structural loads \pm)*

TAS 203-94: *Criteria for Testing Products Subject to Cyclic Wind Pressure Loading (Cyclic load testing \pm)*

Florida Building Code test protocols

ASTM E 1886-05: *Standard Test Method for Performance of Exterior Windows, Curtain Walls, Doors and Storm Shutters Impacted by Missile(s) and Exposed to Cyclic Pressure Differentials*

ASTM E 1996-05: *Standard Specification for Performance of Exterior Windows, Glazed Curtain Walls, Doors and Storm Shutters Impacted by Wind Borne Debris in Hurricanes*

AST M E 330-02: *Test Method for Structural Performance of Exterior Windows, Curtain Walls and Doors by Uniform Static Air Pressure Difference*

AAMA 1304-02: *Voluntary Specification for Forced Entry Resistance of Side-Hinged Door Systems*