

ClearGuard® Storm Panels

Ten Year Limited Warranty

ClearGuard Polycarbonate Panels are warranted against breakage due to manufacturing defect for a period of ten years from the date of sale. This warranty applies to panels fabricated, installed, stored and cleaned according to the manufacturer's recommendations, as detailed in this document. If failure occurs within the warranty period, the purchaser will receive a free replacement ClearGuard Panel when the failed panel, original sales receipt and this warranty are provided to Transparent Protection Systems or the original ClearGuard Dealer.

ClearGuard Panels are further warranted against excessive yellowing due to manufacturing defect as defined in this document, and according to this schedule: If excessive yellowing, due to manufacturing defect and as defined in the Conditions section of this document, occurs after five years from the sale date and before ten years from the sale date, Transparent Protection Systems, Inc. will replace the panel at a cost to the purchaser of 1/120th of the original purchase price for each month after the date of sale.

CONDITIONS:

This warranty only applies to panels that are fabricated, installed, cleaned and stored according to the manufacturer's recommendations, as detailed in this document. ClearGuard Panels are not warranted against abrasion (surface scratches). This warranty does not cover any directly or indirectly related expenses for fabrication, installation or any other losses which may result from the failure of the panel.

Yellowing: The ΔYI (delta change in Yellowness Index) of ClearGuard panels cleaned and stored according to Transparent Protection Systems' recommendations, shall be 7 or less after a five year period from the date of sale, and 12 or less after a ten year period from the date of sale, as measured in accordance with ASTM D 1925 using a Hunter Ultrascan spectrophotometer.

Breakage: While no material can be classified as absolutely unbreakable due to misapplication or improper usage, ClearGuard Storm Panels are warranted against breakage due to manufacturing defect for ten years from the date of sale when fabricated, cleaned and stored according to Transparent Protection Systems' recommendations.

THIS WARRANTY DOES NOT COVER LOSS OF LIGHT TRANSMISSION, ABRASION RESISTANCE OR YELLOWING CAUSED BY THE ACCUMULATION OF DIRT, ATMOSPHERIC PARTICULATE DEPOSITS OR CHANGES IN THE PANEL STRUCTURE, OR EXPOSURE TO ADVERSE OR HAZARDOUS CHEMICAL OR ENVIRONMENTAL SUBSTANCES OR CONDITIONS AS DETERMINED BY THE MANUFACTURER. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE.

TRANSPARENT PROTECTION SYSTEMS' SOLE OBLIGATION AND LIABILITY, AND THE PURCHASER'S SOLE AND EXCLUSIVE REMEDY, IN CONNECTION WITH THIS PANEL OR IT'S USE OR APPLICATION, WHETHER BASED ON WARRANTY, CONTRACT, TORT (INCLUDING NEGLIGENCE) OR ANY OTHER LEGAL THEORY, SHALL BE STRICTLY LIMITED TO REPLACEMENT OF THIS PANEL, OR AT TRANSPARENT PROTECTION SYSTEMS' OPTION, A REFUND OF THE ORIGINAL PURCHASE PRICE OF THIS PANEL. IN NO EVENT SHALL TRANSPARENT PROTECTION SYSTEMS BE LIABLE FOR ANY INDIRECT, INCIDENTAL, CONSEQUENTIAL, SPECIAL OR EXEMPLARY DAMAGES, NOR DAMAGE CAUSED BY FAILURE OF ANY CLEARGUARD PANEL CAUSED BY WINDS EXCEEDING THE TEST STANDARDS OF SBCCI (SSTD 12-99).

Limited warranty is to be completed by the ClearGuard Dealer on the date of sale. See the reverse side for registration information as well as recommended cleaning and storage instructions.



ClearGuard® Storm Panels

Cleaning and Storage Instructions

Regular cleaning with compatible cleansers coupled with proper storage of ClearGuard Hurricane Panels will significantly improve the cosmetic appearance and extend the service life of the panels.

1. When removing panels after storm season, take care to note installation placement.
2. Rinse with clean water to remove excess dust & dirt.
3. Wash with soap or mild detergent using a sponge or soft cloth.
4. Rinse thoroughly with clean water. Dry with a soft, lint-free cloth or chamois to avoid water spots.
5. Store panels in a clean environment and place in a dry area out of the elements.
6. Stack panels in a safe manner. Standing up panels against wall is unsafe. Consult with Dealer/Installer.

Compatible Cleaners

- Formula 409₁
- Top Job, Joy₂
- Palmolive Liquid₃
- Windex with Ammonia D₄

DO NOT use solvents or aromatic hydrocarbons such as gasoline or oil on ClearGuard Panels. Exposure to solvents will chemically attack the material and significantly reduce the clarity and impact strength of the panel.

Warranty Registration

This portion must be completed by an Authorized ClearGuard Dealer at the time of sale.

Dealer Name & Location _____

Purchaser's Name & Address _____

Date of Sale _____ Job/Project Name _____

Dealer Name _____ PO # _____

Lot Number (begins with LN, and is located on each panel) _____

© Registered Trademark of Transparent Protection Systems, Inc.

1 Registered Trademark The Clorox Company

2 Registered Trademark of Proctor & Gamble

3 Registered Trademark of Colgate Palmolive

4 Registered Trademark of Drackett Products Company